



Modular residual current device Type B, 230 V AC, LCD, 50/60 Hz, IDN 30 mA 1A, 0 2000 Hz

Model	
product brand name	SETRON
product designation	modular residual current device
design of the product	Digital, type B
adjustable response delay time	
• initial value	0.06 s
• full-scale value	10 s
frequency of the measuring circuit rated value	
• minimum	0 Hz
• maximum	2 000 Hz
protection class IP at connection all terminals	IP20
type of connectable summation current transformer	5SV8701-2KK, 5SV8701-2KP, 5SV8702-2KK, 5SV8702-2KP, 5SV8703-2KK, 5SV8704-2KK
overvoltage category	III
degree of pollution	3
type of voltage of the operating voltage for actuation	AC
operating voltage	
• rated value minimum	184 V
• rated value maximum	276 V
• at AC rated value	230 V
protection class IP on the front	IP30
Dissipation	
power loss [V·A] maximum	6.5 VA
Main circuit	
operating frequency rated value	
• minimum	50 Hz
• maximum	60 Hz
Auxiliary circuit	
number of CO contacts for auxiliary contacts	2
Relay contacts	
switching voltage of relay contacts rated value	250 V
switching current of relay contacts rated value	5 A
Product function	
product function	
• residual current display	Yes
• error memory	Yes
• password protection	Yes
Connections	
product component removable terminal for main circuit	No
product component removable terminal for auxiliary and control	Yes

circuit	
wire length to the summation current transformer	10 m
stripped length	8 mm
connectable conductor cross-section for flexible conductor	
• minimum	0.2 mm ²
• maximum	2.5 mm ²
connectable conductor cross-section for rigid conductor	
• minimum	0.2 mm ²
• maximum	4 mm ²
tightening torque with screw-type terminals	
• minimum	0.5 N·m
• maximum	0.6 N·m
type of connectable conductor cross-sections for AWG cables for supply voltage	AWG 24 ... AWG 14
type of electrical connection	screw-type terminals

Mechanical Design

height	85 mm
width	36 mm
depth	64 mm
fastening method	DIN rail
net weight	150 g
material of the enclosure	PC

Environmental conditions

influence of the surrounding temperature	Max. 95% humidity
ambient temperature during storage	
• minimum	-25 °C
• maximum	55 °C

Certificates

reference code	
• according to EN 61346-2	F
• according to IEC 81346-2	F

Approvals Certificates

General Product Approval	other
--------------------------	-------



[Confirmation](#)



[Miscellaneous](#)

[Confirmation](#)

other	Environment
-------	-------------

[Miscellaneous](#)

[Environmental Confirmations](#)

Further information

Siemens has decided to exit the Russian market (see here).

<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SV8101-4KK>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SV8101-4KK>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SV8101-4KK

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

last modified:

8/13/2023 

