

product type designation



Figure similar

PROFIBUS connector

SIPLUS DP PROFIBUS plug with PG - 90 degrees based on 6ES7972-0BB70-0XA0 with conformal coating, -40...+70 °C, connection plug for PROFIBUS up to 12 Mbps, 90° cable outlet, insulation displacement method FastConnect, with PG socket

transfer rate

transfer rate / with PROFIBUS DP	9.6 kbit/s ... 12 Mbit/s
----------------------------------	--------------------------

mechanical data

locking mechanism design	Screwed joint
--------------------------	---------------

ambient conditions

ambient temperature	
• during operation	-40 ... +70 °C
• during storage	-40 °C
• during transport	-40 °C
• in horizontal mounting position / during operation	70 ... -40 °C
• during storage and transport	70 ... -40 °C
installation altitude / at height above sea level / maximum	5000 m
ambient condition / relating to ambient temperature - air pressure - installation altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
relative humidity	
• with condensation / maximum	100 %; RH incl. condensation/frost permitted (no commissioning in bedewed state)
• with condensation / according to IEC 60068-2-38 / maximum	100 %; RH incl. condensation / frost (no commissioning in bedewed state), horizontal installation
resistance to biologically active substances	
• conformity according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
• conformity according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
resistance to chemically active substances	
• conformity according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
• conformity according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
resistance to mechanically active substances	
• conformity according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust; *
• conformity according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
environmental category / according to IEC 60721 / note	* The supplied plug covers must remain in place over the unused interfaces during operation!
coating / for equipped printed circuit board / according to EN 61086	Yes; Class 2 for high reliability
type of coating	
• protection against pollution according to EN 60664-3	Yes; Type 1 protection
• for electronic devices in railway applications according to EN 50155	Yes; protective coating of the Class PC2 according to EN 50155:2026

type of test / of the coating / according to MIL-I-46058C	Yes; Discoloration of coating possible during service life
product conformity / of the coating / Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A	Yes; Conformal coating, Class A
protection class IP	IP20
standards, specifications, approvals	
certificate of suitability	
• RoHS conformity	Yes
reference code	
• according to IEC 81346-2	XG
further information / internet links	
internet link	
• to web page: selection aid TIA Selection Tool • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center • to website: Selection guide for cables and connectors • to website: Image database • to website: CAx-Download-Manager • to website: Industry Online Support	http://www.siemens.com/snst http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter https://sie.ag/2QdlxcP http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com

last modified:

9/7/2023 