



In-line fuse switch disconnecter 3-pole selectable, Sz. 2 I=400 A, U=690 V Screw terminal M12, Current transformer installation possible

Model	
product brand name	SENTRON
product designation	Fuse switch disconnectors
design of the product	in in-line design
type of switching contact double breaking switching contact	No
design of the auxiliary release	Without
design of the safety monitoring	Without
design of the load switch strip form	Yes
General technical data	
number of poles	3
number of poles note	3-pole switchable
type of device	For busbar system 185 mm
size of fuse link	NH1, NH2
fuse system	LV HRC fuse
Voltage	
insulation voltage rated value	1 000 V
operational current	- at AC-21 B at 400 V rated value 400 A - at AC-21 B at 500 V rated value 400 A - at AC-21 B at 690 V rated value 400 A - at AC-23 B at 400 V rated value 400 A
operating voltage	- at AC rated value 690 V - at DC rated value 440 V
Protection class	
protection class IP on the front	IP30
Dissipation	
power loss [W]	- for rated value of the current at AC in hot operating state per pole 16.3 W - maximum 49 W
Main circuit	
operational current	- rated value 400 A - with capacitive load at 400 V rated value 216 A - with capacitive load at 500 V rated value 165 A
Suitability	
suitability for operation	System protection
suitability for use	No
main switch	No

• switch disconnecter	Yes
• EMERGENCY OFF switch	No
• safety switch	No
• maintenance/repair switch	No

Product details

product component	
• voltage trigger	No
• undervoltage release	No
• undervoltage release with leading contact	No

Short circuit

conditional short-circuit current (I_q)	
• at AC-21 B at 400 V rated value	110 kA
• at AC-21 B at 500 V rated value	110 kA
• at AC-21 B at 690 V rated value	110 kA
• at AC-22 B at 400 V rated value	110 kA
• at AC-22 B at 500 V rated value	110 kA
• at AC-22 B at 690 V rated value	110 kA
• at AC-23 B at 400 V rated value	110 kA
• at AC-23 B at 500 V rated value	110 kA
• at AC-23 B at 690 V rated value	110 kA

Connections

arrangement of electrical connectors for main current circuit	Screw terminal
type of electrical connection for main current circuit	screw-type terminals

Mechanical Design

height	662 mm
width	100 mm
depth	195 mm
fastening method	Flachanschluss, M 12
mounting position	vertical
busbar center-to-center spacing	185 mm
busbar center-to-center spacing	
• 40 mm	No
• 50 mm	No
• 60 mm	No
• 100 mm	No
• 185 mm	Yes
net weight	5.24 kg

Environmental conditions

ambient temperature during operation	
• minimum	-25 °C
• maximum	55 °C

Approvals Certificates

General Product Approval

other



[Confirmation](#)



[Miscellaneous](#)

[Confirmation](#)

Environment

[Environmental Confirmations](#)

Further information

Siemens has decided to exit the Russian market (see here).
<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an

EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NJ4133-3BF11>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3NJ4133-3BF11>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NJ4133-3BF11

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

last modified:

7/29/2022 

