



SETRON, cylindrical fuse link, 22x58 mm, 100 A, gG, Un AC: 500 V

Model	
product brand name	SETRON
product designation	Cylindrical fuse link
General technical data	
operating class of the fuse link	gG
size of the fuse link	22x58 mm
type of voltage of the operating voltage	AC
supply voltage at DC	250 V
operating voltage at AC rated value	500 V
Dissipation	
power loss [W]	8.4 W
power loss [W] for rated value of the current at AC in hot operating state per pole	8 W
Main circuit	
operational current rated value	100 A
Product details	
product component striker	No
Mechanical Design	
mounting position	Any, preferably vertical
net weight	53 g
Approvals Certificates	
General Product Approval	other




[Confirmation](#)



[Confirmation](#)

[Miscellaneous](#)

Further information
Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/109813875
Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/lowvoltage/catalogs
Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NW6230-1
Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/ww/en/ps/3NW6230-1
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NW6230-1
CAX-Online-Generator http://www.siemens.com/cax
Tender specifications http://www.siemens.com/specifications



last modified:

7/13/2023 

