



electronically configurable signaling column, conventional, 15 segments, without acoustics, M12 plug, 8-pole

product brand name	SIRIUS
product designation	Electronically configurable signaling column
design of the product	standard signaling column
General technical data	
number of light segments	15
product function adjustable optical signal	Yes
product function adjustable acoustic signal	No
type of interface for parameter assignment	USB-C
type of parameterization	Software
type of voltage of the operating voltage	DC
operating voltage at DC rated value	24 V
relative positive tolerance of the operating voltage	10 %
relative negative tolerance of the operating voltage	10 %
insulation voltage (Ui) rated value	50 V
impulse withstand voltage (Uimp) rated value	330 V
operational current rated value	555 mA
consumed current minimum	95 mA
inrush current rated value	800 mA
design of external power supply required	SELV/PELV functional extra low voltage
overvoltage category	I
degree of pollution	3
reference code according to IEC 81346-2:2019	P
operating resource protection class according to IEC 61140	III
Safety related data	
MTTFd	33 a
Lamp	
product component light source	Yes
type of light source	RGB-LED, multicolor
service life of LED	50 000 h
color of lens	clear
number of colors adjustable	1 000 000
design of the optical signal	blinking, flashing, continuous, double-flashes, triple-flashes, rotating
product function adjustable luminous intensity	Yes
light intensity	3 ... 12.5 cd
number of signal stages preset	5
design of the signal stages preset	
• 1	White/Continuous light/3 light segments
• 2	Blue/Continuous light/3 light segments
• 3	Green/Continuous light/3 light segments
• 4	Yellow/Continuous light/3 light segments

• 5	Red/Continuous light/3 light segments
flash frequency	1 Hz
flashing frequency	
• 1	1 Hz
• 2	2 Hz
• 3	3 Hz
Communication	
protocol is supported IO-Link protocol	No
Enclosure	
height	372 mm
width	72 mm
outer diameter	72 mm
material	PC
color of the enclosure	black
fastening method	floor mounting, pipe mounting, angle mounting
protection class IP	IP66/IP69k
degree of protection NEMA rating	4/4X/12/13
type of electrical connection	M12 plug, 8-pole
Ambient conditions	
ambient temperature during operation	-30 ... +60 °C
Approvals Certificates	
General Product Approval	EMV





[Confirmation](#)



other	Environment
Confirmation	Environmental Confirmations

Further information
Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/109813875 Information- and Downloadcenter (Catalogs, Brochures,...) https://www.siemens.com/ic10 Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8WD4615-5HH37 Cax online generator http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=8WD4615-5HH37 Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/ww/en/ps/8WD4615-5HH37 Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=8WD4615-5HH37&lang=en



1	WH = White	Input 1
2	BN = Brown	Input 2
3	GE = Green	Input 3
4	YE = Yellow	Input 4
5	GY = Grey	Input 5
6	PK = Pink	Input 6
7	BU = Blue	COM
8	RD = Red	+24 V