



auxiliary switch for 5SG7230 and 3NW7430

Model	
product brand name	SETRON
product designation	auxiliary switches
design of the product	Mountable
design of the product factory mounted	No
Supply voltage	
operating voltage	
• rated value	230 V
Breaking Capacity	
switching capacity current rated value	2 A
Control current	
type of voltage of control voltage	AC
Product details	
number of fault signal contacts	0
number of NC contacts	0
number of NO contacts	0
number of CO contacts	1
product extension can be mounted	others
product extension	Auxiliary current switch
Mechanical Design	
net weight	9 g
Approvals Certificates	
General Product Approval	other



[Confirmation](#)



[Miscellaneous](#)

[Confirmation](#)

Environment

[Environmental Con-
firmations](#)

[Environmental Con-
firmations](#)

Further information

Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SH5525>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SH5525>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SH5525

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

last modified:

10/11/2023 

