



SENTRON, 3KC transfer switching equipment, manually operated, MTSE, size: 4, 3-pole, Iu: 500 A, Ue AC: 415 V, Ie at AC-33 B at 415 V: 500 A, Ie at AC-23 A at 690 V: 500 A, Screw mounting, front operating mechanism, at the left end, without handle, busbar connection

Model	
product brand name	SENTRON
product designation	3KC transfer switching equipment
design of the product	manually operated
display version for switch position indicator door-coupling rotary operating mechanism	I ON- O OFF- II ON
design of the actuating element	Without handle
design of handle	without
type of the driving mechanism	Front operating mechanism
type of the driving mechanism motor drive	No
General technical data	
number of poles	3
type of device	fixed mounting
size of switch disconnector	4
mechanical service life (operating cycles) for function sequence O-I-O typical	8 000
I2t value	
with closed switch for combination switch + fuse at 500 V maximum	3 687 500 A²·s
with closed switch at 690 V for combination switch + gG fuse maximum	4 450 000 A²·s
of the fuse at 415 V maximum permissible	5 400 005 A²·s
of the fuse at 500 V maximum permissible	5 400 005 A²·s
of the gG fuse at 690 V maximum permissible	3 760 005 A²·s
with closed switch for combination switch + fuse at 415 V maximum	3 687 500 A²·s
position of the switch operating mechanism	at the left end
overvoltage category	IV
degree of pollution	3
insulation voltage	
rated value	1 000 V
Protection class	
protection class IP	IP00
protection class IP	
with closed switch with cover or cable lug cover	IP20
on the front	IP00
Dissipation	
power loss [W]	
with conventional rated thermal current per device	45 W
Main circuit	
operating power	

at AC-23 A at 400 V at 50/60 Hz rated value	280 kW
at AC-23 A at 500 V rated value	355 kW
operational current rated value	500 A
Auxiliary circuit	
number of connected NC contacts for auxiliary contacts	0
number of connected NO contacts for auxiliary contacts	0
number of connected CO contacts for auxiliary contacts	0
number of CO contacts for auxiliary contacts	0
number of NC contacts for auxiliary contacts	16
number of NO contacts for auxiliary contacts	16
suitability for use main switch	Yes
suitability for use switch disconnecter	Yes
suitability for use EMERGENCY OFF switch	Yes
suitability for use safety switch	Yes
suitability for use maintenance/repair switch	Yes
product feature interlock	No
product extension auxiliary switch	Yes
product extension optional	
motor drive	No
voltage trigger	No
Short circuit	
short-circuit current making capacity (Icm) for switch disconnecter	
at 415 V AC without fuse link according to IEC 60947-6-1 rated value minimum	63 kA
at 690 V AC without fuse link according to IEC 60947-3 rated value minimum	63 kA
conditional short-circuit current with line-side fuse protection	
at 415 V by gG fuse according to IEC 60947-6-1 rated value	100 kA
at 415 V by gG fuse rated value	100 kA
at 500 V by gG fuse according to IEC 60947-3 rated value	100 kA
at 690 V by gG fuse according to IEC 60947-3 rated value	65 kA
Connections	
type of connectable conductor cross-sections for aluminum conductor stranded with lug	1x (25 ... 240 mm²), 2x (25 ... 240 mm²)
type of connectable conductor cross-sections	
with combination of Al conductor+switch	500 A / 2x 240 mm²
for copper busbar	1x (40x10 mm²), 2x (40x5 mm²)
type of connectable conductor cross-sections for copper conductor	
stranded with lug according to DIN 46234	1x (25 ... 240 mm²), 2x (25 ... 240 mm²)
stranded with lug according to DIN 46235	1x (25 ... 240 mm²), 2x (25 ... 240 mm²)
type of electrical connection	
for main current circuit	busbar connection
Mechanical Design	
height	235 mm
width	319 mm
depth	232.5 mm
fastening method	screw fixing
fastening method	
4-hole front mounting	No
front mounting with central attachment	No
rail mounting	No
net weight	13 750 g
Environmental conditions	
ambient temperature during operation	
minimum	-25 °C
maximum	70 °C
ambient temperature during storage	

- minimum
- maximum

-50 °C
80 °C

Approvals Certificates

General Product Approval



[Confirmation](#)



EG-Konf.



[Miscellaneous](#)

General Product Approval

Test Certificates

Marine / Shipping

other



[Type Test Certificates/Test Report](#)



[Miscellaneous](#)

[Confirmation](#)

Environment

[Environmental Confirmations](#)

[Environmental Confirmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3KC0344-0QE00-0AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3KC0344-0QE00-0AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3KC0344-0QE00-0AA0

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

