

PS2 keyboard 19", en, with trackball, built-in keyboard for devices with corresponding interface, scope of supply: 1 keyboard



Figure similar

| General information                              |                                                                  |
|--------------------------------------------------|------------------------------------------------------------------|
| Product type designation                         | PS/2 built-in keyboard INT                                       |
| Control elements                                 |                                                                  |
| Keyboard fonts                                   |                                                                  |
| • Design                                         | Membrane keyboard                                                |
| • Keyboard assignment                            | B3F, 101/102 or 104/105 OMRON                                    |
| • Color of the buttons                           | light gray                                                       |
| • Color of the key inscription                   | Black                                                            |
| • Key illumination                               | No                                                               |
| • Function keys                                  |                                                                  |
| — Number of function keys                        | 12                                                               |
| — Programmable                                   | Yes                                                              |
| • Number pad                                     | Yes; Free-standing                                               |
| • status LED displays                            | Yes; Num, Caps and Scroll                                        |
| — for number pad                                 | Yes                                                              |
| — for Shift keys                                 | Yes                                                              |
| Connection type                                  |                                                                  |
| • USB                                            | Yes; With PS/2 USB adapter (not included in the scope of supply) |
| • PS/2                                           | Yes                                                              |
| Frame size/design                                |                                                                  |
| • Standard                                       | Yes; For industrial applications                                 |
| • 19" keyboard                                   | Yes                                                              |
| Installation type/mounting                       |                                                                  |
| Rack mounting                                    | No                                                               |
| Front mounting                                   | Yes                                                              |
| Wall mounting/direct mounting                    | No                                                               |
| Input current                                    |                                                                  |
| Current consumption (rated value)                | 35 mA; Typical                                                   |
| Battery                                          |                                                                  |
| Battery-operated                                 | No; maintenance-free                                             |
| EMC                                              |                                                                  |
| Emission of radio interference acc. to EN 55 011 |                                                                  |
| • Limit class A, for use in industrial areas     | Yes                                                              |
| Degree and class of protection                   |                                                                  |
| IP (all-round)                                   | IP65 when the ball is actuated; mouse only IP55                  |
| Splashproof                                      | Yes                                                              |
| Standards, approvals, certificates               |                                                                  |
| CE mark                                          | Yes                                                              |
| RoHS conformity                                  | Yes                                                              |

|                                                   |                                                                                                                                                                                 |
|---------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Ambient conditions</b>                         |                                                                                                                                                                                 |
| Ambient temperature during operation              |                                                                                                                                                                                 |
| • min.                                            | 0 °C                                                                                                                                                                            |
| • max.                                            | 40 °C                                                                                                                                                                           |
| Ambient temperature during storage/transportation |                                                                                                                                                                                 |
| • min.                                            | -10 °C                                                                                                                                                                          |
| • max.                                            | 50 °C                                                                                                                                                                           |
| Relative humidity                                 |                                                                                                                                                                                 |
| • Operation, max.                                 | 90 %; no condensation                                                                                                                                                           |
| • Condensation permissible                        | No                                                                                                                                                                              |
| <b>Operating systems</b>                          |                                                                                                                                                                                 |
| Runs under operating system                       |                                                                                                                                                                                 |
| • Windows CE                                      | Yes                                                                                                                                                                             |
| • Windows Vista                                   | Yes                                                                                                                                                                             |
| • Windows XP                                      | Yes                                                                                                                                                                             |
| • Windows 7                                       | Yes                                                                                                                                                                             |
| • Windows 10                                      | Yes                                                                                                                                                                             |
| <b>Mechanics/material</b>                         |                                                                                                                                                                                 |
| Material                                          |                                                                                                                                                                                 |
| • Sheet steel                                     | Yes                                                                                                                                                                             |
| Enclosure material (front)                        |                                                                                                                                                                                 |
| • Plastic                                         | Yes; AUTOTEX (R) V150                                                                                                                                                           |
| Service life                                      |                                                                                                                                                                                 |
| • Number of operating cycles, keys                | 1 000 000; Operations (minimum)                                                                                                                                                 |
| <b>Dimensions</b>                                 |                                                                                                                                                                                 |
| Width                                             | 482.6 mm                                                                                                                                                                        |
| Height                                            | 38 mm                                                                                                                                                                           |
| Depth                                             | 177.8 mm                                                                                                                                                                        |
| <b>Weights</b>                                    |                                                                                                                                                                                 |
| Weight (without packaging)                        | 1 490 g                                                                                                                                                                         |
| Weight (with packaging)                           | 1 735 g                                                                                                                                                                         |
| <b>Scope of supply</b>                            |                                                                                                                                                                                 |
| Delivery quantity in pieces                       | 1; Built-in keyboard with stud bolts                                                                                                                                            |
| <b>Other</b>                                      |                                                                                                                                                                                 |
| Merchandise                                       | Yes; TIPRO no. K-842 (K-642)                                                                                                                                                    |
| Manufacturer name                                 | TIPRO Representative Office                                                                                                                                                     |
| Manufacturer's address                            | Vogelweg 20, 31785 Hameln, Germany                                                                                                                                              |
| Target devices                                    | Suitable for IPC and HMI devices with the corresponding interfaces (see manual)                                                                                                 |
| Note:                                             | Suitable PS/2 USB adapter (keyboard/mouse): 1x USB 1.1, plug A on 2x PS/2 sockets, 0.20 m, black; manufacturer: Renkforce; supply by Conrad Elektronik, order no.: 1360251 - 62 |
| Usable in the following products                  |                                                                                                                                                                                 |
| • Product 1                                       | <a href="#">6AV2124-0GC13-0AX0</a>                                                                                                                                              |
| • Product 2                                       | <a href="#">6AV2124-0QC13-0AX0</a>                                                                                                                                              |

last modified:

9/29/2021 