

Specifications



Photo is representative



Eaton FNM-3

Eaton Bussmann series FNM fuse, Time-delay, 3 A, Dual, Non-indicating, Ferrule end x ferrule end, 10 kAIC at 125 Vac, 100 AIC at 250 Vac, Nickel-plated bronze endcap, Standard, 250 V

General specifications

PRODUCT NAME	Eaton Bussmann series FNM fuse
CATALOG NUMBER	FNM-3
UPC	051712520300
EAN	5027590449496
PRODUCT LENGTH/DEPTH	0.39 in
PRODUCT HEIGHT	1.44 in
PRODUCT WIDTH	0.39 in
PRODUCT WEIGHT	0.2 lb
WARRANTY	Not Applicable
COMPLIANCES	CE Marked RoHS Compliant



Powering Business Worldwide

Electrical rating

AMPERAGE RATING	3 A
INTERRUPT RATING	10 kAIC at 125 Vac 100 AIC at 250 Vac
VOLTAGE RATING	250 V

General information

CONNECTION	Ferrule end x ferrule end
FUSE INDICATOR	Non-indicating
SPECIAL FEATURES	Superior overload and cycling capabilities

Physical details

MATERIAL	Nickel-plated bronze endcap
NUMBER OF ELEMENTS	Dual
PACKAGING TYPE	Standard

Resources

CATALOGS	Bussmann series complete full line catalog no. 1007
MULTIMEDIA	Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - FNM-3
TECHNICAL DATA SHEETS	FNM-3~BUSS MIDGET FUSE
TECHNICAL SERVICE BULLETINS	Datasheet - FNQ-30

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

