

Specifications



Photo is representative



Eaton DS7-340SX070N0-N

Eaton DS7 soft start controller, Frames 3 and 4, 70 A, 50 hp, 480 V, 24 Vac/Vdc, Internal bypass, IP20, HJD3250 circuit breaker, 200 A class RK5 max fuse, Generation 7 series

General specifications

PRODUCT NAME	Eaton DS7 soft start controller
CATALOG NUMBER	DS7-340SX070N0-N
UPC	786685856742
PRODUCT LENGTH/DEPTH	6.34 in
PRODUCT HEIGHT	5.47 in
PRODUCT WIDTH	3.66 in
PRODUCT WEIGHT	3 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
COMPLIANCES	CE Marked C-Tick Compliant
CERTIFICATIONS	CSA Certified IEC 60947-4-2 EN 60947-4-2 UL Listed
CATALOG NOTES	No internal radio interference suppression filters

Product specifications

BYPASS	Internal
CONTROL VOLTAGE	24 Vac/Vdc
HORSEPOWER	50 hp
PHASE	Three-phase mains supply voltage
TYPE	Soft start controller
VOLTAGE RATING	480 V
FUSE SIZE	200 A class RK5 max
CIRCUIT BREAKER TYPE	HJD3250
FRAME SIZE	3 4
ENVIRONMENTAL RATING	IP20
SERIES	Generation 7
RATED OPERATIONAL CURRENT	70 A

Resources

CATALOGS	Solid-State Motor Control, Reduced Voltage Motor Starters, Volume 6, Tab 1
MULTIMEDIA	Soft Starter Product Family Overview Soft Starter DS7 up to 32 A Soft starter DS7 up to 200 A
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - DS7-340SX070N0-N

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

