

Specifications



Photo is representative



Eaton FNM-4/10

Eaton Bussmann series FNM fuse, Time-delay, 0.4 A, Dual, Non-indicating, Ferrule end x ferrule end, 35 AIC at 250 Vac, 10 kAIC at 125 Vac, Nickel-plated bronze endcap, Standard, 250 V

General specifications

PRODUCT NAME	Eaton Bussmann series FNM fuse
CATALOG NUMBER	FNM-4/10
UPC	051712520041
EAN	5027590449557
PRODUCT LENGTH/DEPTH	0.39 in
PRODUCT HEIGHT	1.44 in
PRODUCT WIDTH	0.39 in
PRODUCT WEIGHT	0.2 lb
WARRANTY	Not Applicable
COMPLIANCES	CE Marked RoHS Compliant



Powering Business Worldwide

Electrical rating

AMPERAGE RATING	0.4 A
INTERRUPT RATING	10 kAIC at 125 Vac 35 AIC at 250 Vac
VOLTAGE RATING	250 V

General information

CONNECTION	Ferrule end x ferrule end
FUSE INDICATOR	Non-indicating
SPECIAL FEATURES	Superior overload and cycling capabilities

Physical details

MATERIAL	Nickel-plated bronze endcap
NUMBER OF ELEMENTS	Dual
PACKAGING TYPE	Standard

Resources

CATALOGS	Bussmann series complete full line catalog no. 1007 FNM-4/10~FNM-4-10~BUSS MIDGET FUSE
MULTIMEDIA	Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - FNM-4/10

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

