

Specifications



Photo is representative



Eaton KTK-12

Eaton Bussmann series KTK fuse, Control circuits, Lighting circuit protection, Meter circuits, 12 A, Non-indicating, Ferrule end x ferrule end, 100 kAIC at 600 V, Nickel-plated bronze endcap, Melamine tube, 600 V

General specifications

PRODUCT NAME	Eaton Bussmann series KTK fuse
CATALOG NUMBER	KTK-12
UPC	051712420082
EAN	5027590445825
PRODUCT LENGTH/DEPTH	0.41 in
PRODUCT HEIGHT	1.5 in
PRODUCT WIDTH	0.41 in
PRODUCT WEIGHT	0.19 lb
WARRANTY	Not Applicable
COMPLIANCES	CE Marked RoHS Compliant



Powering Business Worldwide

Electrical rating

AMPERAGE RATING	12 A
INTERRUPT RATING	100 kAIC at 600 Vac
VOLTAGE RATING	600 V

General information

CONNECTION	Ferrule end x ferrule end
FUSE INDICATOR	Non-indicating
SPECIAL FEATURES	Small footprint

Physical details

MATERIAL	Melamine tube Nickel-plated bronze endcap
PACKAGING TYPE	Standard

Resources

CATALOGS	Bussmann series complete full line catalog no. 1007
MULTIMEDIA	Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - KTK-12
TECHNICAL DATA SHEETS	KTK-12~LIMITRON FAST ACTING FUSE
TECHNICAL SERVICE BULLETINS	Datasheet - FNQ-30

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

