

Specifications

Eaton CCP2-1-30CF

Eaton Bussmann series CCP UL98 fusible disconnect, Finger Safe, Lock-On provision, 600 Vac, 125 Vdc, 225A, UL98 fusible disconnect, Three-pole, 200 kA - CCP2-1-30CF

General specifications

PRODUCT NAME	Eaton Bussmann series CCP UL98 fusible disconnect
CATALOG NUMBER	CCP2-1-30CF
UPC	051712709248
PRODUCT LENGTH/DEPTH	4.5 in
PRODUCT HEIGHT	3 in
PRODUCT WIDTH	1 in
PRODUCT WEIGHT	3.7 lb
WARRANTY	Not Applicable
CERTIFICATIONS	UL 98

Electrical rating

AMPERAGE RATING	30A
FREQUENCY RATING	50/60 Hz
SHORT-CIRCUIT RATING	200 kA
VOLTAGE RATING	347 Vac, 125 Vdc

General information

SPECIAL FEATURES	Finger Safe, 1/4" LOTO
SUITABLE FOR FUSES	TCF6 to TCF30 TCF1RN to TCF30RN FCF1RN to FCF30RN

Physical details

FUSE TYPE	CUBEFuse
NUMBER OF POLES	Single-pole

Resources

	CCP2-1-30CF~CCP2 1P 30A CF
CATALOGS	Bussmann series complete full line catalog no. 1007
CERTIFICATION REPORTS	Eaton Bussmann EU Declaration of conformity 93-68-EEC2512
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - CCP2-1-30CF

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

