

Specifications



Photo is representative



Eaton 216615

Eaton Moeller® series M22 Pushbutton,
RMQ-Titan, Flat, maintained, White, Blank,
Bezel: titanium

General specifications

PRODUCT NAME	Eaton Moeller® series M22 pushbutton
CATALOG NUMBER	216615
MODEL CODE	M22-DR-W
EAN	4015082166151
PRODUCT LENGTH/DEPTH	30 mm
PRODUCT HEIGHT	30 mm
PRODUCT WIDTH	30 mm
PRODUCT WEIGHT	0.011 kg
COMPLIANCES	CE Marked
CERTIFICATIONS	EN 60947-5 IEC 60947-5 CSA Std. C22.2 No. 14-05 CSA Std. C22.2 No. 94-91 UL 508 VDE CSA IEC/EN 60947 CSA File No.: 012528 IEC/EN 60947-5 UL CSA Class No.: 3211-03 CSA-C22.2 No. 94-91 UL Category Control No.: NKKR UL File No.: E29184 CE CSA-C22.2 No. 14-05 VDE 0660 DNV GL LR
GLOBAL CATALOG	216615
PRODUCT TYPE	Pushbutton



Powering Business Worldwide

Product specifications

TYPE	Pushbutton actuator
ACTUATOR COLOR	White
ACTUATOR FUNCTION	Maintained Switching function latching
10.10 TEMPERATURE RISE	Not applicable.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Please enquire
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION	Does not apply, since the

Resources

CATALOGS

[eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf](#)

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

DECLARATIONS OF CONFORMITY

[eaton-pushbutton-declaration-of-conformity-uk251341en.pdf](#)

[eaton-pushbutton-declaration-of-conformity-uk251340en.pdf](#)

[eaton-operating-pushbutton-m22-dimensions-004.eps](#)

[eaton-operating-pushbutton-m22-dimensions-003.eps](#)

[eaton-operating-actuation-m22-dimensions-002.eps](#)

DRAWINGS

[eaton-operating-samrtwire-m22-3d-drawing.eps](#)

[eaton-general-approval-m22-symbol.eps](#)

[eaton-operating-button-symbol-013.eps](#)

[eaton-general-m22-symbol.eps](#)

[eaton-general-m22-standards.eps](#)

ECAD MODEL

[ETN.216615.edz](#)

INSTALLATION INSTRUCTIONS

[IL04716002Z](#)

MCAD MODEL

[DA-CS-drucktaste_flach](#)

[DA-CD-drucktaste_flach](#)

SPECIFICATIONS AND DATASHEETS

[Eaton Specification Sheet - 216615](#)

AGAINST ELECTRIC SHOCK	entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
FITTED WITH:	Front ring
OPERATING FREQUENCY	1800 Operations/h
BUTTON COLOR	White
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
CONNECTION TO SMARTWIRE-DT	With SWD-RMQ connections Yes
ACTUATING FORCE	5 N
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT STORAGE TEMPERATURE - MAX	80 °C
AMBIENT STORAGE TEMPERATURE - MIN	40 °C
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
FORCE FOR POSITIVE OPENING - MIN	0 N
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
NUMBER OF COMMAND POSITIONS	1
OPENING DIAMETER	22.5 mm

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
BEZEL COLOR	Titanium
SHOCK RESISTANCE	Mechanical, According to IEC/EN 60068-2-27 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
BEZEL MATERIAL	Plastic
DESIGN	Flat Classical
MOUNTING POSITION	As required
DEGREE OF PROTECTION	IP66 NEMA 12 NEMA 4X IP69K NEMA 3R NEMA 13 IP67
DEGREE OF PROTECTION (FRONT SIDE)	IP67/IP69K NEMA 4X
INSCRIPTION	Blank
FRONT ELEMENT TYPE	Flat
FUNCTIONS	Stay-put/spring-return function can be changed on device
LENS TYPE	Round
LIFESPAN, MECHANICAL	1,000,000 Operations (AC operated)
STATIC HEAT DISSIPATION, NON- CURRENT-DEPENDENT PVS	0 W
PRODUCT CATEGORY	RMQ-Titan
SIZE	Front dimensions: 22 x 22 mm

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

