

Specifications

Eaton KTK-2

Eaton Bussmann series KTK fuse, Control circuits, Lighting circuit protection, Meter circuits, 2 A, Non-indicating, Ferrule end x ferrule end, 100 kAIC at 600 V, Melamine tube, Nickel-plated bronze endcap, 600 V

General specifications

PRODUCT NAME	Eaton Bussmann series KTK fuse
CATALOG NUMBER	KTK-2
UPC	051712420129
EAN	5027590063500
PRODUCT LENGTH/DEPTH	0.41 in
PRODUCT HEIGHT	1.5 in
PRODUCT WIDTH	0.41 in
PRODUCT WEIGHT	0.017 lb
WARRANTY	Not Applicable
COMPLIANCES	RoHS Compliant CE Marked
PRODUCT TYPE	Fuse

Electrical rating

AMPERAGE RATING	2 A
INTERRUPT RATING	100 kAIC at 600 Vac
VOLTAGE RATING	600 V

General information

CONNECTION	Ferrule end x ferrule end
FUSE INDICATOR	Non-indicating
SPECIAL FEATURES	Small footprint

Physical details

MATERIAL	Melamine tube Nickel-plated bronze endcap
PACKAGING TYPE	Standard

Resources

	Bussmann series complete full line catalog no. 1007
CATALOGS	Bussmann series full line catalog 1007, section 01-low voltage branch circuit fuses
MULTIMEDIA	Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - KTK-2
TECHNICAL DATA SHEETS	KTK-2~LIMITRON FAST ACTING FUSE
TECHNICAL SERVICE BULLETINS	Datasheet - FNQ-30

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

