

Specifications



Photo is representative



Eaton KLM-3/4

Eaton Bussmann series KLM fuse, DC Control circuits, DC photovoltaic systems, 0.75 A, Non-indicating, 50 kAIC at 600 Vdc, 100 kAIC at 600 Vac, Nickel-plated bronze endcap, Melamine tube, Standard, 600 V, 600 Vdc

General specifications

PRODUCT NAME	Eaton Bussmann series KLM fuse
CATALOG NUMBER	KLM-3/4
UPC	051712695060
EAN	5027590256087
PRODUCT LENGTH/DEPTH	0.001 in
PRODUCT HEIGHT	0.001 in
PRODUCT WIDTH	0.001 in
PRODUCT WEIGHT	0.18 lb
WARRANTY	Not Applicable
COMPLIANCES	RoHS Compliant CE Marked
PRODUCT TYPE	Fuse



Powering Business Worldwide

Electrical rating

AMPERAGE RATING	0.75 A
INTERRUPT RATING	50 kAIC at 600 Vdc 100 kAIC at 600 Vac
VOLTAGE RATING	600 Vac, 600 Vdc

General information

FUSE INDICATOR	Non-indicating
SPECIAL FEATURES	Non-indicating

Physical details

MATERIAL	Melamine tube Nickel-plated bronze endcap
PACKAGING TYPE	Standard

Resources

CATALOGS	Bussmann series complete full line catalog no. 1007 KLM-3/4~KLM-3-4~LIMITRON FAST ACTING FUSE
	Bussmann series Fuseology
MULTIMEDIA	
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - KLM-3/4

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

