



Figure similar

AS-i compact module K45 digital A/B slave, 4 DI, IP67 4 x input, maximum 200 mA 4 x M8 socket Screw version Mounting plate 3RK1901-2EA00 or 3RK1901-2DA00 is to be ordered separately

General technical data	
design of the product	digital I/O modules for operation in the field, IP67 - K45
Type	4 inputs
design of the slave type	A/B slave
I/O configuration	0
ID/ID2 code	A/0
Number I/O sockets	4
type of electrical connection of the inputs and outputs	M8 screw-type terminals
AS interface total current input max	270 mA
operating voltage according to AS-Interface specification	26.5 ... 31.6 V
Ground terminal	not available
Addressing	front addressing socket
AS interface Connection Polarity reversal protection	built-in
Delivery note	the modules are delivered without mounting plate
Sensor supply	
type of voltage supply for power supply	using AS-Interface
input voltage	20 ... 30 V
property of the sensor supply short-circuit and overload resistant	Yes
ampacity of the sensor supply for all inputs at ambient temperature 40 °C	200 mA
Inputs	
number of digital inputs	4
type of connection technology	2- and 3-wire technology
Input circuit	PNP transistor
type of voltage of the input voltages	DC
Inputs switching level High min	10 V
input current at digital input - for signal <1> minimum - with signal <0> maximum	6 mA 1.5 mA
Inputs sensor supply using AS-Interface	short-circuit and overload resistant
Inputs socket assignment - PIN 1 - PIN 3 - PIN 4	sensor supply L+ sensor supply L- data input
design of the pin assignment of the inputs	standard assignment
Outputs	
number of digital outputs	0

Display		
Status display - display of I/Os - display of Uaux - display of AS-Interface/diagnostics		yellow LED not required green/red dual LED
Assignment of the data bits		
Assignment of data bits - socket - socket 2 - socket 3 - socket 4		PIN 4 = IN1 (D0) PIN 4 = IN2 (D1) PIN 4 = IN3 (D2) PIN 4 = IN4 (D3)
Ambient conditions		
ambient temperature - during operation - during storage		-25 ... +85 °C -40 ... +85 °C
protection class IP		IP67
Mechanical data		
width		45 mm
height		80 mm
depth		30 mm
fastening method		standard rail mounting/wall mounting using mounting plate for K45 compact module
shock resistance		15g / 11 ms
Certificates/ approvals		
General Product Approval		EMC Declaration of Conformity



[Confirmation](#)



Marine / Shipping



other



[Confirmation](#)

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RK2200-0CT20-0AA3>

Cax online generator


<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RK2200-0CT20-0AA3>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RK2200-0CT20-0AA3>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RK2200-0CT20-0AA3&lang=en



last modified:

3/11/2021 [🔗](#)