



SITOR cylindrical fuse link, 14x51 mm, 15 A, aR, Un AC: 690 V, Un DC: 600 V, DC according to UL, Striker indicator

Model	
product brand name	SENTRON
product designation	SITOR cylindrical fuse link
design of the product	DC acc. to UL
design of an identification indicator	Striker indicator
General technical data	
operating class of the fuse link	aR
size of the fuse link	14x51 mm
type of voltage / of the operating voltage	AC
supply voltage / at DC	600 V
operating voltage / at AC / rated value	690 V
Dissipation	
power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	5.5 W
operational current / at AC / rated value	15 A
Main circuit	
operational current / rated value	15 A
Product details	
product component / striker	Yes
Mechanical Design	
mounting position	Any, preferably vertical
net weight	23 g
General Product Approval	
Declaration of Conformity	

[Confirmation](#)



other

[Miscellaneous](#)

[Environmental Conformations](#)

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NC1415-5>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3NC1415-5>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NC1415-5

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



