

Electr. Buzzer EM Contin/pulse 24VDC BK



Part No.: 111.000.55

**MECHANICAL DATA**

Height	72 mm
Diameter	50 mm
Materials	PC PC/ABS
Housing colour	Black
Protection category	IP65
Connection	Screw terminals
cross-sectional area maximum	1,50mm ² / 16AWG
Type of fixing	Built-in mounting
Acoustic service life	5,000 h minimum
Working temperature minimum	-20°C
Working temperature maximum	+50°C
Weight with packaging	50 g
Product weight	40 g

ELECTRICAL DATA

Operating voltage	24V
Operating voltage type	DC
Operating voltage tolerance	+/- 10%
Rated operational voltage	24 VDC
Rated operational current	25 mA
Rated inrush current	350 mA
Protection class	Protection class 2
Pollution degree	3
	In the connection area: 2

ACUSTICAL DATA

Volume/dB(max) at 1m distance	80,0 dB (A)
Acoustic signal image	Continuous tone Pulse tone
Audio frequency	2800 Hz



For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.

DRAWING

Technical drawing of a mechanical part, likely a valve or actuator, showing three views: a side view, a front view, and a cross-section view.

Dimensions:

- Side View:
 - Total height: 51
 - Flange height: 45
 - Small gap: 1
 - Distance from flange to start of thread: 20,7
- Front View:
 - Outer diameter: Ø50
 - Threaded section diameter: Ø22,5
 - Thread specification: M22x1,5
- Cross-section View:
 - Inner diameter: Ø28
 - Threaded section diameter: Ø22,5
 - Distance from center to thread start: 13,6
 - Distance from center to thread end: 3,2

Part Number: 111

For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.