



Sample image

LATERAL AUXILIARY CONTACTS


for KG20 - KG317 and KH(R)16 - KH(R)25B

Designation: K1.H010/A11-VE

Kind of contact operation: "A" not overlapping

Contact combination: "11" 1 NO + 1 NC

Type of mounting: "-VE" for type of mounting VE

IEC 60947-3 EN 60947-3, VDE 0660 Teil 107						
Märkdriftspänning Ui						
			Spänning (V) AC / DC			
			690 AC			
UL60947-4-1 , UL508						
Nominal Voltage						
			Spänning (V) AC / DC			
			600 AC			
Märkdriftspänning Ui						
			Spänning (V) AC / DC			
			600 AC			
Rated thermal current						
		Ström (A)	Omgivningstemperatur (°C)		Additional Text	
		10	0 - 40		-	
Pilot duty rating code						
Duty Code						
A600						
General Use						
AC / DC	Spänning (V)	Ström (A)	No. of phases	No. of poles	No. of contacts in series	
AC	600	10	1	1	1	
General Information						
Text						
- Använd endast kopparkabel. Kabeln får inte förtennas.						
CSA						
Temp. rating of wire						
			Temperature rating (°C)	Ström (A)	Text	
			75	-	only	
GENERAL TECHNICAL INFORMATION						
Size of conductor						
composition of conductor	Min. / Max. value		No. of conductor per terminal	Cross section (mm²) or (AWG/kcmil)		Material of the wire
flexible wire	Max.			2 2,5mm²		Copper
flexible wire	Max.			2 AWG 14		Copper
Single-core or stranded wire	Max.			2 AWG 12		Copper
Single-core or stranded wire	Max.			2 2,5mm²		Copper
flexible wire with ferrule according to DIN 46228	Max.			2 2,5mm²		Copper
Stripping length						
			Length (mm) -			
			8			
Rekomenderad skruvmejsel						
Typ av skruvmejsel			Value			
Stjärnskruvmejsel			PH1			
Slot screwdriver according to DIN 5264			0,8x4			
KG20 - KG100C						
						
31	43					
32	44					