


Pin busbar, 10 mm² connection: 3-phase/+ 8x phase touch-safe for 1FI, 4-pole, NLI+8LS, 1-pole



Model		
product brand name	SENTRON	
product designation	Pin busbar	
design of the product	10 mm², 3PH,RCCB NLI+8XPH	
General technical data		
phase number	3	
cross-section	10 mm²	
Main circuit		
operational current rated value	63 A	
Product details		
product feature insulated	Yes	
Connections		
type of electrical connection	Pin	
Mechanical Design		
width	9.2 mm	
length	192 mm	
net weight	68.8 g	
General Product Approval		other
Declaration of Conformity		

[Confirmation](#)

[Miscellaneous](#)



[Miscellaneous](#)

other	Environment
-------	-------------

[Confirmation](#)

[Environmental Con-
firmations](#)

Further information

Siemens has decided to exit the Russian market (see here).

<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3667>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5ST3667>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3667


CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>





last modified:

7/9/2021

