



DELTA fläche IP44, AP Dark gray/light gray OFF switch, 10A 250V 66x 75 mm, with lamp +2 windows (neutral, light)

| Model                           |  |                                |                                       |       |             |
|---------------------------------|--|--------------------------------|---------------------------------------|-------|-------------|
| product brand name              |  |                                | DELTA                                 |       |             |
| type of installation switch     |  |                                | rotary switch                         |       |             |
| type of light source            |  |                                | Lighting with glow lamp               |       |             |
| type of composition             |  |                                | basic element with complete enclosure |       |             |
| design of the actuating element |  |                                | rocker/button                         |       |             |
| General technical data          |  |                                |                                       |       |             |
| type of switch                  |  |                                | OFF switch 1-pole                     |       |             |
| mounting type                   |  |                                | surface mounting                      |       |             |
| surface processing              |  |                                | others                                |       |             |
| material                        |  |                                | others                                |       |             |
| Supply voltage                  |  |                                |                                       |       |             |
| operating voltage rated value   |  |                                | 250 V                                 |       |             |
| Protection class                |  |                                |                                       |       |             |
| protection class IP             |  |                                | IP44                                  |       |             |
| Switching capacity              |  |                                |                                       |       |             |
| switching capacity current      |  |                                | 10 A                                  |       |             |
| Main circuit                    |  |                                |                                       |       |             |
| operational current rated value |  |                                | 10 A                                  |       |             |
| Appearance                      |  |                                |                                       |       |             |
| appearance                      |  |                                | shiny                                 |       |             |
| color                           |  |                                | grey                                  |       |             |
| Product details                 |  |                                |                                       |       |             |
| product component               |  |                                |                                       |       |             |
| • labeling field                |  |                                | No                                    |       |             |
| • signaling contact             |  |                                | No                                    |       |             |
| • pushbutton switch             |  |                                | No                                    |       |             |
| product feature halogen-free    |  |                                | Yes                                   |       |             |
| Number                          |  |                                |                                       |       |             |
| number of actuating rockers     |  |                                | 1                                     |       |             |
| Connections                     |  |                                |                                       |       |             |
| type of electrical connection   |  |                                | Plug-in terminal                      |       |             |
| Mechanical Design               |  |                                |                                       |       |             |
| height                          |  |                                | 82 mm                                 |       |             |
| depth                           |  |                                | 47 mm                                 |       |             |
| fastening method                |  |                                | screw mounting                        |       |             |
| material of the enclosure       |  |                                | plastic                               |       |             |
| General Product Approval        |  | Declaration of Con-<br>formity | Test Certificates                     | other | Environment |



[Miscellaneous](#)

[Confirmation](#)

[Environmental Confirmations](#)

#### Further information

**Siemens has decided to exit the Russian market (see here).**

<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

**Siemens is working on the renewal of the current EAC certificates.**

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

**Information on the packaging**

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5TA4711>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/5TA4711>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5TA4711](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TA4711)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>



