



SITOR fuse link, with slotted blade contacts, NH3, In: 160 A, aR, Un AC: 1500 V, Un DC: 1000 V, front indicator

Model				
product brand name		SENTRON		
product designation		SITOR fuse link		
design of the product		With slotted blade contacts		
design of an identification indicator		front indicator		
design of the switching contact		with slotted blade contacts for M10 screw fixing. mounting dimension: 210 mm		
design of the fuse link		SITOR, LV HRC design		
General technical data				
size of fuse system according to EN 60269-1		NH3		
operating class of the fuse link		aR		
varying load factor (WL)		1		
type of voltage of the operating voltage		AC/DC		
operating voltage at AC according to UL rated value		1 500 V		
Supply voltage				
supply voltage				
• at AC rated value		1 500 V		
• at DC		1 000 V		
Switching capacity				
switching capacity current				
• according to IEC 60947-2 rated value		100 kA		
Dissipation				
power loss [W]		56 W		
power loss [W]				
• for rated value of the current at AC in hot operating state per pole		56 W		
• maximum		56 W		
Product details				
product description		with blade contacts, silver-plated		
accessories included		no		
Mechanical Design				
mounting position		Any, preferably vertical		
net weight		1 995 g		
Environmental conditions				
ambient temperature during operation				
• minimum		-20 °C		
• maximum		50 °C		
environmental category		-20 to +50 at 95% relative humidity		
General Product Approval		Declaration of Conformity	Test Certificates	other

[Confirmation](#)



[Special Test Certificate](#)

[Confirmation](#)

other

Environment

[Miscellaneous](#)

[Miscellaneous](#)

[Environmental Confirmations](#)

Further information

Siemens has decided to exit the Russian market (see here).

<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NE5424-0C>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3NE5424-0C>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NE5424-0C

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



