

FlexSQUARE / LED Double Flash Beacon 853

## LED Double Flash Beacon BWM 115-230VAC R



Part No.: 853.110.60



### MECHANICAL DATA

|                              |                                |
|------------------------------|--------------------------------|
| Length                       | 85 mm                          |
| Width                        | 85 mm                          |
| Height                       | 72 mm                          |
| Materials                    | PC<br>PP-GF                    |
| Dome colour                  | Red                            |
| Housing colour               | Black                          |
| Protection category          | IP66<br>IP67                   |
| Connection                   | Screw terminals                |
| cross-sectional area maximum | 1,50mm <sup>2</sup> / 16AWG    |
| Cable entry                  | Membrane grommet               |
| Cable entry minimum          | d = 1 mm<br>d = 6 mm           |
| Cable entry maximum          | d = 12 mm<br>d = 9 mm          |
| Type of fixing               | Base mounting<br>Wall mounting |
| Working temperature minimum  | -25°C                          |
| Working temperature maximum  | +50°C                          |
| Weight with packaging        | 183 g                          |
| Product weight               | 152 g                          |

### ELECTRICAL DATA

|                             |                              |
|-----------------------------|------------------------------|
| Operating voltage           | 115-230V                     |
| Operating voltage type      | AC                           |
| Operating voltage frequency | 50Hz at 230V<br>60Hz at 115V |
| Operating voltage tolerance | +/- 10%                      |
| Rated operational voltage   | 230 VAC                      |
| Rated operational current   | 180 mA                       |
| Rated inrush current        | 7.000 mA                     |
| Protection class            | Protection class 2           |
| Pollution degree            | 3                            |
| Overvoltage category        | II                           |
| Isolation voltage           | Ui = 250V; Uimp = 2.500V     |

### OPTICAL DATA

|              |     |
|--------------|-----|
| Light source | LED |
| Light colour | Red |



For additional installation and mounting information, refer to the appropriate user guide at [www.werma.com](http://www.werma.com). This printed copy is for information only and is subject to alteration.

FlexSQUARE / LED Double Flash Beacon 853

**LED Double Flash Beacon BWM 115-230VAC R**

|                      |                  |
|----------------------|------------------|
| Optical signal image | Double flash     |
| Flash frequency      | 1 Hz             |
| Service life optical | 50,000 h maximum |

**APPROVAL DATA**

|                             |      |
|-----------------------------|------|
| Conforms with CE            | yes  |
| WEEE                        | yes  |
| Conform with ATEX-directive | no   |
| Conforms with CCC           | yes  |
| Conforms with UL            | nein |
| Conforms with FCC           | no   |
| Conforms with IC            | No   |
| EAC Zertifikat vorhanden    | yes  |
| Conforms with AS-I          | no   |
| ICAO Certification          | No   |
| Conforms with GL            | no   |
| Conforms with RoHS CN       | no   |
| Conforms with VdS           | no   |




For additional installation and mounting information, refer to the appropriate user guide at [www.werma.com](http://www.werma.com). This printed copy is for information only and is subject to alteration.

FlexSQUARE / LED Double Flash Beacon 853

## LED Double Flash Beacon BWM 115-230VAC R

### DRAWING



For additional installation and mounting information, refer to the appropriate user guide at [www.werma.com](http://www.werma.com). This printed copy is for information only and is subject to alteration.